

尺寸:9x7CM CC-02A HE CC-02B

USER MANUAL

4-IN-1 RETRACTABLE CAR CHARGER

10S
Type-C
10W

CC-02A CC-02B

Contents

- Specifications 01
- Overview 03
- Installation Instructions 08
- Retraction Guidelines 10
- Widely Compatible 12
- Parameter Description 13
- Attentions 14
- Customer Service 15

Thank you for purchasing and using this product!
In order to bring you a better experience, please read this operation instruction carefully before using this product and keep it properly for future reference.

Specifications
Model: CC-02A

Product Name	Retractable Car Charger
Model	CC-02A
Material	ABS+PC+PVC
Applicable Place	Car Cigarette Lighter
Colour	Space Gray/Black
Charging Interface	Type-C/Lightning/USB-A/USB-C
Input Voltage	12-24V
Total Output	62W
Type-C	5V/3A, 9V/2.3A, 20W
Lightning	5V/2.4A, 12W
USB-A	5V/3A, 15W
USB-C	5V/3A, 15W
Cable Length	31.5inch/80cm

Model: CC-02B

Product Name	Retractable Car Charger
Model	CC-02B
Material	ABS+Aluminum Alloy+PC+PVC
Applicable Place	Car Cigarette Lighter
Colour	Space Gray/Black
Charging Interface	Type-C/Lightning/USB-A/USB-C
Input Voltage	12-24V
Total Output	78W
Type-C	5V/3A, 9V/3A, 12V/2.5A, 30W
Lightning	5V/3A, 9V/2A, 18W
USB-A	5V/3A, 15W
USB-C	5V/3A, 15W
Cable Length	31.5inch/80cm

The above data is obtained from laboratory experiments. The actual parameters may differ from product to product or other factors. All images shown here are for reference only.

Overview

Compact Size

1. The small and compact design make the car charger easy to carry and doesn't take up your car space. It's suitable for various car models, addressing the challenge of limited space inside the car.

Flexible Retractable Design

2. This product's retractable cable has flexible stretching and retracting functions, making organization and storage a breeze. It enhances usability while preventing cable entanglement.

All-Round Protections

3. Multiple protection mechanisms, including overvoltage, overcurrent, over-temperature, short circuit, etc. Built-in high-toughness spring supports over 10,000 rebounds, enhancing product stability and prolonging its lifespan.

Multi-Fast Charging Protocol Certification

Supporting various fast charging protocols including PD, QC3.0, AFC, MTK, and FCP. The four USB ports simultaneously support high-speed fast charging for your devices, meeting your charging needs of various devices at once.

TYPE-C
CC-02A: 20W fast charging cable
CC-02B: 30W fast charging cable

Lightning
CC-02A: 12W fast charging cable
CC-02B: 18W fast charging cable

USB-A
15W fast charging port

USB-C
15W fast charging port

Installation Instructions

1. Insert the car charger into your vehicle's car cigarette lighter socket, and push down to the bottom to secure it.

2. After installation, the charger can be adjusted left and right, with a maximum tilt of 180°.

Retraction Guidelines

Pull Out the Charging Cables

1. Pull out to the desired length.

2. Once you hear a click sound, the length is fixed.

Retract the Charging Cables

3. Pulling out the charging cable by 0.4inch-0.8inch.

4. Release it and retract automatically.

Widely Compatible

Widely compatible with smartphone like iPhone 15/14/13/12 series, Samsung series, Huawei series, tablet, earphone, game devices, USB-C devices, drones and so on.

Parameter Description

1. When using the Type-C interface, model CC-02A adaptive output can reach 5V/3A, 9V/2.3A, 20W Max; model CC-02B adaptive output can reach 5V/3A, 9V/3A, 12V/2.5A, 30W Max.

2. When using the Lightning interface, model CC-02A adaptive output can reach 5V/2.4A, 12W Max; model CC-02B adaptive output can reach 5V/3A, 9V/2A, 18W Max.

3. When using USB-A, model CC-02A and model CC-02B adaptive output can reach 5V/3A, 15W.

4. When using USB-C, model CC-02A and model CC-02B adaptive output can reach 5V/3A, 15W.

ONLY Model CC-02B: Supports simultaneous super fast charging for Lightning interface, Type-C interface, USB-A, and USB-C interfaces.
Total output: Up to 78W.

Attentions

- Children please use under the guidance and accompanied by an adult.
- This product has the function of input over current and over voltage protection. The improper use will shut down or reduce the output power. Please check whether the device is abnormal or improperly used.
- Please do not disassemble.
- Ensure proper connection of the Retractable Car Charger and avoid using damaged charging cables.
- Keep the operating ambient temperature between 32-104°F. Avoid placing the product in water or near open flames. Do not expose it to extremely high temperatures (>104°F) or very low temperatures (<-32°F).
- Incorrect use or improper placement of the product by the user may lead to a reduction in the service life of the product or damage to the product. The consequence thus incurred is not within the scope of the warranty or the manufacturer's responsibility. We hope you can kindly understand.
- In case of any unusual occurrences, cease using the Retractable Car Charger immediately and contact our customer service.

Customer Service

- 24 month limited warranty
- Lifetime technical support
- support@ohlpro.com
- @OHLPRO
- @OHLPRO
- @OHLPRO Inc
- https://ohlpro.com

If you have any questions or concerns about our products, please feel free to contact us. We'd be more than happy to help and answer you. Thank you for your attention and support to our products, we look forward to establishing a good cooperative relationship with you.

CE FC RE MADE IN CHINA

Shenzhen Hengyehui Technology Co., Ltd.
Address: Ximnu Community, Pinghu Street, Longgang District, Shenzhen, No. 1 Building, Building 1, Area A, Zhanmiling Industrial Zone
Business cooperation: support@ohlpro.com
Website: https://ohlpro.com
Shenzhen Hengyehui Technology Co., Ltd. All Rights Reserved.